



**WALL MOUNTED SINGLE
SHADE SCREEN**

WALL MOUNTED SINGLE SHADE SCREEN

WA-I320-WM/ WA-I430-WM/ WA-I490-WM/
WA-I550-WM

DESCRIPTION

The Wall-Mounted Single Shade Screen is a sleek and efficient window display solution designed for high-impact visibility. This single-shade screen mounts effortlessly on walls, providing a clean, modern look while showcasing your content with vibrant clarity. Ideal for retail environments and digital signage, it ensures your messages stand out with its sharp resolution and elegant design. Its space-saving installation and effective performance make it a perfect choice for enhancing customer engagement and visual appeal. The Wall-Mounted Single Shade Screen combines elegance and efficiency, making it an ideal choice for high-impact window displays. Offered in 43, 49, 55, and 65 inches, it provides display areas of 945.8 x 533.8 mm, 1078.8 x 608.8 mm, 1213.8 x 684.8 mm, and 1432.8 x 807.8 mm. With a sharp 1080 x 1920 resolution and an impressive brightness of 2500 nits, this screen delivers vibrant, eye-catching visuals that stand out in any setting. Its sleek, wall-mounted design not only enhances visibility but also saves space, making it perfect for retail and digital signage applications.



SPECIFICATIONS

Size	43 Inch	49 Inch	55 Inch	65 Inch
Product Name	WA-I320-WM	WA-I430-WM	WA-I490-WM	WA-I550-WM
Resolution	1080*1920	1080*1920	1080*1920	1080*1920
Display Size	945.8*533.8mm	1078.8*608.8mm	1213.8*684.8mm	1432.8*807.8mm
Brightness	2500 nits	2500 nits	2500 nits	2500 nits
View Angle	89/89/89/89(U/D/L/R)	89/89/89/89(U/D/L/R)	89/89/89/89(U/D/L/R)	89/89/89/89(U/D/L/R)
OPS	Android 11	Android 11	Android 11	Android 11
Main Chip	RK3568, Quad-core, The main frequency is up to 2.0GHz	RK3568, Quad-core, The main frequency is up to 2.0GHz	RK3568, Quad-core, The main frequency is up to 2.0GHz	RK3568, Quad-core, The main frequency is up to 2.0GHz
Ram+Rom	2+32G	2+32G	2+32G	2+32G
External Interface	HDMI Input, VGA Input, RJ45, USB*2	HDMI Input, VGA Input, RJ45, USB*2	HDMI Input, VGA Input, RJ45, USB*2	HDMI Input, VGA Input, RJ45, USB*2
Installation Method	Wall mounted bracket, Hanging	Wall mounted bracket, Hanging	Wall mounted bracket, Hanging	Wall mounted bracket, Hanging
Dimensions		964.2mm 553.7mm 63mm		1236.55mm 708.7mm 63mm
Packing Size		1080mm 160mm 670mm		1350mm 160mm 840mm
Net/Gross Weight		19kg/22kg		31kg/34kg
Input Voltage	AC 110V ~ 240V 50/60HZ	AC 110V ~ 240V 50/60HZ	AC 110V ~ 240V 50/60HZ	AC 110V ~ 240V 50/60HZ

APPLICATION



FINANCE



EDUCATION



RETAIL



PROPERTY
MANAGEMENT



RESIDENCIAL



HEALTH CARE



GOVERNMENT



PUBLIC FACILITIES



ENERGY



ENTERPRISE